

ITEM 4: VEHICLE No. 39

One (1) 2013 Ford F550 Cab and Chassis with Utility Body with all standard equipment and warranties and including the following:

CODE	DESCRIPTION
X5H	Super Cab 4x4
660A	Order Code XL
162"	Wheel Base 60" CA
99T/44W	6.7L 4V Diesel V8 Engine/6 Speed Auto Transmission
68M	Payload Upgrade Package
X8L	4.88 Limited Slip Rear Differential
Z1	Oxford White Clearcoat
AS	HD Vinyl 40/20/40 Seats – Steel Color
535	Trailer Tow High Capacity
52B	Tow Command Integrated Trailer Brake
90L	Power Equipment Group
18B	6" Angular Black Running Boards
76C	Backup Alarm
THB	225/70Rx19.5(G) BSW Traction Tires (4 Traction and 2 Steer)
Beacon Light	Star 200SHL/to be mounted on Service Body Window Screen
Multi Flash LED's	ECCO 3965X(2 ea) to be mounted on Rear of Service Body
Service Body	See Attached Specifications.

SERVICE BODY

One (1) Stahl Model MD108VVD-54 Medium Duty Service Body

- 110" long.
- 96" wide.
- Inside bed width 54" wide floor.
- Galvanized steel construction.
- 60" CA.

Compartmentation

- Front vertical compartments: one per side 60" high, 20" deep with (4) adjustable shelves per compartment with dividers.
- Rear vertical compartments: one per side 60" high, 20" deep with (2) adjustable shelves per compartment with dividers.
- Horizontal compartments: one per side over rear wheels even with top of front and rear compartments. Double doors in lieu of standard. One full width bolt in shelf per side. Shelves to be provided but NOT installed.
- Over center spring door holders on all vertical doors.
- All locks and latches to be stainless, "T" type handles.
- Compartment interior bottoms to be coated with bed liner.

Service Body Electrical/Lighting

- (1) Star 200 SHL LED Beacon Light mounted on top of rear window screen wired to cab upfitter switches.
- All marker lights to be LED (markers, stop, tail, turn).

- (2) Amber LED multi-flash lights installed in rear compartments wired to cab upfitter switches; Ecco Pt#3965x.
- Trailer plug to be 7 pole split pin; Cole Hersee Pt#12063.
- All wiring, lights, plugs, and switches to be heat shrunk and soldered.

Body Base/Miscellaneous

- Master lock push-pull bar locks installed at rear of body on each side.
- Install reinforced rear window screen fabricated with mesh and integrated into front of body between front compartments.
- Grab handles mounted to each rear compartment.
- Rear bumper to be fabricated with gripstrut surface. Bumper to have center recess for hitch.
- 16,000 lb capacity combination pintle hook – 2-⁵/₁₆" hitch to be mounted to rear bumper and mounted at the highest point of rear bumper, approximately 25". Safety D-rings mounted to bumper. Bumper is to be braced with V-bracing to frame.
- (1) 2" receiver tube installed vertically in rear bumper driver side for vice holder. 1" in from outside corner and braced to strengthen the vice.
- Tailgate to be two-point slam-locking.
- Polished fuel fill.
- Service body to be installed on truck chassis.
- Service body to be powder-coated in White.
- Install mudflaps on rear of service body.
- Service body to be undercoated.

NOTICE TO BIDDERS:

- These vehicles must be equipped with all other equipment necessary to conform to NYS Vehicle Law.
- Please call John J. Kuryak at 716-685-8219 if you have any questions. He will return your call as soon as possible.
- Delivery will be within ninety (90) days following receipt of Purchase Order.
- Any exceptions to the specifications must be submitted in writing with the quote. Provide manufacturer's data sheets and sketches where applicable.