




View thousands of Crane Specifications on FreeCraneSpecs.com

PK 72002 Performance - YOUR STRONG PARTNER

The PK 72002 Performance proves its superiority in tough day-to-day duty. The combination of high lifting capacity and low weight, little space requirement and highest user friendliness make it the perfect working tool. The return oil utilisation system installed as standard guarantees highest working speed and economic operation.



EXCLUSIVELY FROM PALFINGER:
AOS - THE ACTIVE OSCILLATION SUPPRESSION SYSTEM



EXTENSIVE STANDARD EQUIPMENT

LEAVES NOTHING TO BE DESIRED

Outrigger system

The 8.6 m outrigger system fitted as standard ensures optimal stability – as an option it can be supplied with support cylinders that can be hydraulically swivelled up 180°. The control valves for crane and additional support are mounted as standard on the base frame. The switchover between crane and support control takes place electrically. Spirit level and hour counter are mounted as standard in the support control valve console.

Control valve

In combination with the PALFINGER radio control system the load sensing proportional valve enables the crane to be adjusted very slightly.

Internally routed oil ducts



The internally routed oil ducts permit a compact design for the extension system and ensure perfect protection from damage.

Endless slewing mechanism

The standard endless slewing mechanism provides an unrestricted action radius. As a result the crane operates much more quickly and cost-efficiently.

Load-holding valves

They prevent the crane arm from dropping and are fitted as standard onto the slewing mechanism, elevating arm, and extension cylinders. The valves are positioned in such a way that they are protected from being damaged.



Additional hinged arms

To extend the range of applications of the PK 72002 Performance additional hinged arms are available in several designs and for various arm versions.

Return oil utilisation

The high speed of the extension system is impressive. It results from return oil utilisation, which is installed as standard, and the generously dimensioned hydraulic lines. This makes for increased efficiency in any type of working!

Functional Design

- Cover in the area of the control valve
- Hoses covered behind the crane column
- Support system with internally routed hydraulic hoses



Hose equipment for accessories

With this option you can provide the oil supply to accessories. The hoses are routed in compact troughs and plastic link chains. They are therefore optimally protected.

AOS

The Active Oscillation Suppression system, which is available exclusively from PALFINGER, compensates for jolts and sharp stress cycles caused by crane operation. Because oscillations are eradicated, the crane can work with pin-point accuracy, much more quickly and therefore more cost-efficiently.



Advanced Package

- Oil cooler mounted
- Electronic HPLS
- Capacity display on control console
- PALFINGER radio control
- PALTRONIC 50
- Functional Design



THE PK 72002 Performance: OUTSTANDING MOVEMENT GEOMETRY

PK 72002 Performance



Max. lifting capacities

PK 72002 Performance A		
hydraulic		
max. Capacity: 22000 kg/48500 lbs		
Outreach	Capacity	
4.4 m 14' 5"	14930 kg	32910 lbs
5.8 m 19' 0"	11400 kg	25130 lbs
7.5 m 24' 7"	8840 kg	19490 lbs



PK 72002 Performance B		
hydraulic		
max. Capacity: 22000 kg/48500 lbs		
Outreach	Capacity	
4.4 m 14' 5"	14730 kg	32470 lbs
5.8 m 19' 0"	11190 kg	24670 lbs
7.5 m 24' 7"	8630 kg	19030 lbs

PK 72002 Performance C		
hydraulic		
max. Capacity: 22000 kg/48500 lbs		
Outreach	Capacity	
4.4 m 14' 5"	14480 kg	31920 lbs
5.8 m 19' 0"	10920 kg	24070 lbs
7.5 m 24' 7"	8360 kg	18430 lbs


PK 72002 Performance D		
hydraulic		
max. Capacity: 21970 kg/48430 lbs		
Outreach	Capacity	
4.4 m 14' 5"	14270 kg	31460 lbs
5.8 m 19' 0"	10680 kg	23540 lbs
7.5 m 24' 7"	8100 kg	17860 lbs

PK 72002 Performance E		
hydraulic		
max. Capacity: 21560 kg/47530 lbs		
Outreach	Capacity	
4.4 m 14' 5"	14060 kg	31000 lbs
5.8 m 19' 0"	10450 kg	23040 lbs
7.5 m 24' 7"	7860 kg	17330 lbs


PK 72002 Performance G		
hydraulic		
max. Capacity: 19890 kg/43850 lbs		
Outreach	Capacity	
4.4 m 14' 5"	13720 kg	30250 lbs
5.8 m 19' 0"	10160 kg	22400 lbs
7.5 m 24' 7"	7530 kg	16600 lbs
9.4 m 30' 10"	5730 kg	12630 lbs
11.4 m 37' 5"	4520 kg	9960 lbs
13.7 m 44' 11"	3610 kg	7960 lbs
15.8 m 52' 2"	3050 kg	6720 lbs
18.1 m 59' 5"	2610 kg	5750 lbs
20.4 m 66' 11"	2310 kg	5090 lbs
manual		
22.7 m 74' 6"	1460 kg	3220 lbs
25.0 m 82' 0"	1270 kg	2800 lbs



PK 72002D PJ154C



PK 72002E PJ115D




The reaches are indicated for a 20° main boom position and are therefore not the maximum ones.



PALFINGER ADVANCED PACKAGE AS STANDARD!

PK 72002
Performance

PALFINGER



PK 72002 Performance	
Technical Specifications (DIN 15018 H1-B3)	
Max lifting moment	667.1 kNm 68.0 mt 491850 ft lbs
Max lifting capacity	22000 kg 215.8 kN 48500 lbs
Max hydraulic outreach	20.5 m 67' 3"
Max outreach (with fly jib)	29.7 m 97' 8"
Slewing angle	endless
Slewing torque	44.1 kNm 4.5 mt 32510 ft lbs
one slewing gear	68.7 kNm 7.0 mt 50650 ft lbs
one slewing gear	68.7 kNm 7.0 mt 50650 ft lbs

Executions shown in the leaflet are not always corresponding to standard execution. Design and specification are subject to change without prior notice. Country-specific regulations are to be considered for the crane installation.

STRENGTH, OUTREACH AND PRECISION



PALFINGER

www.palfinger.com